

ACCESSORI / ACCESSORIES

	Codice Code	Nome Name	Dimensioni Dimensions	Materiale Material	Note Notes
	ACC.0101.0	Muffola gel IP68 - 4 vie Waterproof connection box with gel IP68 - 4 channels 3 poli / 3 poles	95x45x24 mm (3,74x1,771x0,944 in)	Nylon 66-RV	Per cavo max For cable max Ø 6,5÷12 mm (Ø 0,255÷0,472 in)
	ACC.0102.0	Muffola gel IP68 - 2 vie Waterproof connection box with gel IP68 - 2 channels 2 poli / 2 poles	31x30x30 mm (1,22x1,181x1,181 in)	Nylon 66-RV	Per cavo max For cable max Ø 9,5÷12 mm (Ø 0,374÷0,472 in)
	ACC.0103.0	Muffola gel IP68 - 2 vie Waterproof connection box with gel IP68 - 2 channels 3 poli / 3 poles	38x30x36 mm (1,496x1,1181x1,417 in)	Nylon 66-RV	Per cavo max For cable max Ø 6÷10 mm (Ø 0,236÷0,393 in)
	ACC.0104.0	Connettore gel IP67 Gel connector IP67	10x8x16 mm (0,393x0,314x0,629 in)	Polycarbonato Polycarbonate	Per cavo / for cable max Ø 2 mm (0,078 in) 0,14÷0,5 mm²
	ACC.0105.0	Morsettiera stagna - 2 vie Watertight thermal block 2 channels 3 poli / 3 poles	Ø26,5x115 mm (Ø1,043x4,527 in)	PA66	Per cavo max For cable max Ø 5÷13 mm (Ø 0,196÷0,511 in)
	ACC.0106.0	Morsettiera stagna - 2 vie Watertight thermal block 2 channels 5 poli / 5 poles	Ø32x130 mm (Ø1,259x5,118 in)	PA66	Per cavo max For cable max Ø 8÷17 mm (Ø 0,314÷0,669 in)
	ACC.0100.0	Muffola gel IP68 - 2 vie Waterproof connection box with gel IP68 - 2 channels 6 poli / 6 poles	59x22x22 mm (2,322x0,866x0,866 in)	Nylon PA-66	Per cavo max For cable max Ø 4÷7 mm (Ø 0,157÷0,275 in)
	ACC.0107.0	Connettore a 2 vie IP65/IP67 Waterproof connection box IP65/IP67 - 2 channels	37x12x12 mm (1,456x0,472x0,472 in) confezione 5 pezzi 5 pieces package	Polycarbonato Polycarbonate	Per cavo / for cable max 0,75 mm² Ø 5,6÷7,4 mm (Ø 0,22÷0,291 in)
	ACC.0005.0	Muffola gel IP67 - 4 vie Waterproof connection box with gel IP67 - 4 channels 3 poli / 3 poles	138x31x12 mm (5,433x1,22x0,472 in)	Nylon PA-66	Per cavo max For cable max Ø 4÷8,5 mm (Ø 0,157÷0,334 in)
	ACC.0147.0	Muffola gel IP67 - 4 vie Waterproof connection box with gel IP67 - 4 channels 5 poli / 5 poles	138x31x12 mm (5,433x1,22x0,472 in)	Nylon PA-66	Per cavo max For cable max Ø 4÷8,5 mm (Ø 0,157÷0,334 in)
	ACC.0021.0	Cavo DMX DMX cable	per m Ø esterno 6,2 mm external Ø 6,2 mm (Ø 0,244")	PVC	Cavo schermato Shielded cable
	ACC.0022.0	Cavo DMX DMX cable	bobina 100 m (328 ft) Ø esterno 6,2 mm external Ø 6,2 mm (Ø 0,244")	PVC	Cavo schermato Shielded cable
	ACC.0025.0	Cavo KNX KNX cable	bobina 50 m (164 ft) Ø esterno 6,1 mm external Ø 6,1 mm (Ø 0,24")	PVC esente piombo PVC lead free	Cavo schermato Shielded cable
	ACC.0039.0	Cavo 3 poli 3 poles cable	bobina 50 m (164 ft) Ø esterno 8,5mm external Ø 8,5mm (Ø 0,334")	Neoprene	Cavo schermato Shielded cable
	ACC.0040.0	Cavo 3+2 poli 3+2 poles cable	bobina 50 m (164 ft) Ø esterno 9,5mm external Ø 9,5mm (Ø 0,374")	Poliuretano Polyurethane	Cavo schermato Shielded cable